

The QuikCONE heater is offered in four module configurations that can be arranged around a specific process or application.

- Offered in four module sizes.
 - #2 series, 10 ½-inch by 21-inch, contains two emitters.
 - #4 series, 10 ½-inch by 42-inch, contains four emitters.
 - BR30, 15-inch by 30-inch, contains two emitters.
 - BR60, 15-inch by 60-inch, contains four emitters.
- Utilizes a high-grade nichrome wire that is helically wrapped around a scientifically engineered ceramic cone-shaped core and encased in a high-mass, hardened sand slurry, creating a durable, highly efficient, long wave infrared emitter.
- Emitter is offered in a variety of wattages:
 - 500W, 650W, 750W, 1000W in the #2 and #4 series
 - 1000W, 1300W, 1500W in the BR series.
- Emitter is offered in a variety of voltages.
 - 95 Volt for 380 Volt systems (four in series)
 - 104 Volt for 208 Volt systems (two in series)
 - 120 Volt for 240 Volt and 480 Volt systems (two or four in series).
 - 150 Volt for 600 Volt systems (four in series).
- Each emitter is mounted within an independent polished stainless steel parabolic reflector, enabling a superior uniform heat pattern.

The Heater Specifications:

Heater Part Number	Series	Input (kW)	Size in Inches			Fig. No.
			H	L	D	
#2-500	#2	1.0	10 1/2	21	5 1/2	1
#2-650	#2	1.3	10 1/2	21	5 1/2	1
#2-750	#2	1.5	10 1/2	21	5 1/2	1
#2-1000	#2	2.0	10 1/2	21	5 1/2	1
#4-500	#4	2.0	10 1/2	42	5 1/2	2
#4-650	#4	2.6	10 1/2	42	5 1/2	2
#4-750	#4	3.0	10 1/2	42	5 1/2	2
#4-1000	#4	4.0	10 1/2	42	5 1/2	2
BR30-1000	BR	2.0	15	30	6 1/2	1
BR30-1300	BR	2.6	15	30	6 1/2	1
BR30-1500	BR	3.0	15	30	6 1/2	1
BR60-1000	BR	4.0	15	60	6 1/2	2
BR60-1300	BR	5.2	15	60	6 1/2	2
BR60-1500	BR	6.0	15	60	6 1/2	2
BR60-1500C	BR	6.0	15	60	6 1/2	2

Note: 208V, 240V, 380V, 480V and 600V are the standard available voltages.

