

ET5-S Standard Ruffneck™ Thermostat



Heavy Duty Line Voltage Thermostat

- Temp. range: 5° to 25°C / 40° to 80°F
- 22 Amps, 277 VAC
- ¾ HP @ 125 VAC
- 1½ HP @ 250/277 VAC
- Single pole
- Single Throw*
- Approximate Shipping Weight: 0.6 lbs. (0.28 kg)

TF115 NEMA 4X Corrosion Resistant Thermostat



- Temp. range: 4° to 30°C / 40° to 90°F
- 25 Amps Res., 480 VAC Max.
- Full load = 16 Amps @ 120 VAC
12 Amps @ 240 VAC
- Lock Rotor = 80 Amps @ 120 VAC
60 Amps @ 240 VAC
- single pole, double throw (heating or cooling applications)
- Approximate Shipping Weight: 0.69 lbs. (0.31 kg)

XTB Explosion-Proof Thermostat



- Temp. range: -18° to 40°C / 0° to 100°F
- Class I, Division 1 & 2 Groups C & D
Class II, Division 1 & 2 Groups E, F & G
Class III, Division 1 & 2
- Remote sensing bulb with 57 in. capillary length
- 15 Amps Res., 600 VAC Max. – 25 Amps Res., 277 Max.
- XTB04481 (Single Pole, Single Throw)*
- XTB04483 (Double Pole, Single Throw)*
- Approximate Shipping Weight: 3.8 lbs. (1.7 kg)

XTWA Explosion-Proof Thermostat



- Temp. range: -18° to 40°C / 0° to 100°F
- Class I, Division 1 & 2 Groups A, B, C & D
Class II, Division 1 & 2 Groups E, F & G
Class III, Division 1 & 2
- Sensing bulb in Finned Thermowell for Air Sensing
- 15 Amps Res., 600 VAC Max. – 25 Amps Res., 277 Max.
- XTWA04481 (Single Pole, Single Throw)*
- XTWA04483 (Double Pole, Single Throw)*
- Approximate Shipping Weight: 4.0 lbs. (1.8 kg)

XTD8-S Explosion-Proof Thermostat



- Temp. range: 5° to 25°C / 40° to 80°F
- Class I, Division 1 & 2 Groups C & D
Class II, Division 1 & 2 Groups E, F & G
Class III, Division 1 & 2
- Feed-thru model (includes explosion-proof plug)
- ¾" - 14 NPT conduit opening (½" conduit adapter included)
- single pole, double throw (heating or cooling applications)
- 22 Amps, 277 VAC Max.
- ¾ HP @ 125 VAC
- 1½ HP @ 250/277 VAC
- Approximate Shipping Weight: 5.3 lbs. (2.4 kg)

NOTE: All 3 phase motors on AH, HP and FR heaters require a motor starter (supplied by others).

*Heating applications only